

# Declaration of Performance

Conforming Regulation (EU) No 305/2011 Annex III  
Construction Products Regulation

## Quartzline SL-EP 2K

DoP06EP2K015

**EN 13813:2002**

### 1. Product Type

Unique identification code of the product-type:

Quartzline SL-EP 2K

### 2. Type

batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

SL-EP 2K

**batch no. refer to packaging**

### 3. Intended use

or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**2-component epoxy self-levelling floor**

**EN 13813: SR - B1,5-AR1-IR4**

### 4. Name, registered trade name

or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Quartzline BV

Daltonstraat 54

3316GD Dordrecht, The Netherlands

### 5. Contact Address

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant (see 4)**

### 6. AVCP

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

**System 4**

### 7. Notified body (hEN)

In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

**Not relevant**

### 8. Notified body (ETA)

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

**Not relevant**


## 9. Declared performance

Essential	Characteristics	Performance Test Standard	Harmonised technical Specification
Release of corrosive Substances	SR	EN 13813	EN 13813
Abrasion Resistance:	≤ AR1 <sup>1)</sup>	EN 13892-4	
Bond strength:	≥ B1,5	EN 13892-8	
Impact resistance:	≥ IR4	EN ISO 6272	
Sound insulation:	NPD <sup>2)</sup>	EN ISO 140-1	
Sound absorption:	NPD	EN ISO 354	
Reaction to fire:	Efl <sup>3)</sup>	EN 13501-1	
Permeability to water vapour:	NPD	EN ISO 7783-1	
Thermal resistance:	NPD	EN 12664	
Chemical resistance:	NPD	EN 13529	

1) Minimum Classification

2) No Performance Determined

3) According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/Efl without further testing



## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dordrecht, 30 Januari 2018



Peter Groeneweg  
 Research and development




Willem van der Marel  
 Quality Control